DESCRIPTION

C23400 is a brass formulated for primary forming into wrought products. It has a moderately high base cost and a moderately high melting temperature relative to other wrought brasses.

CHEMICAL COMPOSITION

Elements	Min (%)	Max (%)			
Cu	81.0	84.0			
Pb	715 516	0.05			
Fe	Allie Helle Bullet	0.05			
Total Others	Julia III Oddili -	0.20			
Zn	Ren	nainder			

MECHANICAL PROPERTIES ACCORDING TO ASTM B134 (AS PER TEMPER H02)

	Range (Inch)	From	То	UTS Min (Mpa)	UTS Max (Mpa)	PS Min	Elongation Min (%)	Hardness Min	Hardness Max
300	Round (Dia)	1.5	6.00	540.00	620.00	-	-	2111 ²² - 3	5 lillin - 0.07 lillin
	Hex (A/F)	3.00	6.00	540.00	620.00	-	11 - 15°	- ⁰ P ₁ ₁ ₁ ₁	-
	Square (A/F)	3.00	6.00	540.00	620.00	[] - [] []	-69/11/1	-	- 4

PHYSICAL PROPERTIES

No Physical Properties for this alloy.

FABRICATION PROPERTIES

Technique	Suitability				
Soldering	Excellent				
Brazing	Excellent				
Capacity for being hot worked	Good				
Gas Shielded Arc Welding	Good				
Coated Metal Arc Welding	Not Recommended				
Spot Weld	Fair				
Seam Weld	Not Recommended				
Butt Weld	Good				
Capacity for Being Cold Worked	Excellent				
Capacity for Being Hot Formed	Good				
Machinability Rating	30				

TYPICAL USES

- > Welded Wire
- > Filer Metal