### **DESCRIPTION**

Brass is an alloy mainly consisting of copper and zinc. Brass alloys can be easily shaped and are available in various colors. Brass has high thermal conductivity. CZ129 forging brass alloys have good forgeability. They are available in the form of rod.

The following datasheet gives details about CZ129 brass alloys.

### **CHEMICAL COMPOSITION**

Elements	Min (%)	Max (%)
Cu	58.50	61.00
Pb	0.80	1.50
Fe I	BUILTY - THE	0.20
Total Others Excl. Fe	E SETTE STEET STEET	0.50
Zn	Remai	nder

## MECHANICAL PROPERTIES ACCORDING TO BS2874 (AS PER TEMPER M)

Range (Inch)	From	То	UTS Min (N/mm²)	PS Min	Elongation Min (%)	Hardness Min	Hardness Max
Round (Dia)	1.5	18.00	380.00	.ad	25.00	Ph. Jan	-
	18.00	40.00	380.00	- 11/2 -	25.00	-	N. Palin
	40.00	75.00	350.00	-	28.00	-77,1972	
Hex (A/F)	3.00	18.00	380.00		25.00	. UE T	thilling -
	18.00	40.00	380.00	- Ellips	25.00	phills -	-
	40.00	70.00	350.00	<u> </u>	28.00	-	
Square (A/F)	3.00	18.00	380.00	422.	25.00	ZIN <sup>2</sup>	ie iii - opiji
	18.00	40.00	380.00	-	25.00	The Party of the Party	-
	40.00	60.00	350.00	- This	28.00		- 1
Rectangle (Thickness)	3.00	18.00	380.00		25.00	-	THE - TENE
	18.00	40.00	380.00	4p3/1" -	25.00	THE - TEN	O. T. Hilliam
	40.00	50.00	350.00	-	28.00	Jille - OF High	-

# PHYSICAL PROPERTIES

Melting Point - Liquidus°F	1640	
Melting Point - Solidus°F	1620	
Densitylb/cu in. at 68°F	0.305	
Specific Gravity	8.44	
Electrical Conductivity% IACS at 68°F		
Thermal ConductivityBtu/ sq ft/ ft hr/ °F at 68°F		
Coefficient of Thermal Expansion 68-57210 <sup>-6</sup> per °F (68 – 572°F)		
Specific Heat CapacityBtu/ lb /°F at 68°F	0.09	
Modulus of Elasticity in Tensionksi		
Modulus of Rigidityksi	5600	
	Melting Point - Solidus°F  Densitylb/cu in. at 68°F  Specific Gravity  Electrical Conductivity% IACS at 68°F  Thermal ConductivityBtu/ sq ft/ ft hr/ °F at 68°F  Coefficient of Thermal Expansion 68-57210 <sup>-6</sup> per °F (68 – 572°F)  Specific Heat CapacityBtu/ lb /°F at 68°F  Modulus of Elasticity in Tensionksi	

# **FABRICATION PROPERTIES**

Technique	Suitability			
Soldering	Excellent			
Brazing	Good			
Oxyacetylene Welding	Not Recommended			
Gas Shielded Arc Welding	Not Recommended			
Coated Metal Arc Welding	Not Recommended			
Spot Weld	Not Recommended			
Seam Weld	Not Recommended			
Butt Weld	Fair			
Capacity for Being Cold Worked	Poor			
Capacity for Being Hot Formed	Excellent			
Forgeability Rating	100			
Machinability Rating	80			
7527				

#### **TYPICAL USES**

- > Builders Hardware
- > Building
- > Consumer
- > Electrical
- > Industrial